VEVOR

Upgrade · The Home Creator Way

Dent Puller Kit

MODEL: XPT9019



VEVOR Support Center

This is the original instruction, please read all manual instructions carefully before operating. VEVOR reserves a clear interpretation of our user manual. The appearance of the product shall be subject to the product you received. Please forgive us that we won't inform you again if there are any technology or software updates on our product.

	Warning-To reduce the risk of injury, user must read instructions manual carefully.
	This symbol, placed before a safety comment, indicates a kind of precaution, warning, or danger. Ignoring this warning may lead to an accident. To reduce the risk of injury, fire, or electrocution, please always follow the

	recommendation shown below.
	Warning- Be sure to wear eye protectors when using this product.
	Warning- Be sure to wear gloves when using this product.

WARNING

Note: Please use it correctly in accordance with the instructions to avoid affecting the prod uct repair effect.

1. Wear ANSI-approved safety goggles and heavy-duty work gloves during use.
2. Keep away from children. This product is not a toy. Do not allow children to play with or near this item.
3. Use as intended only.
4. Inspect before every use; do not use if parts are loose or damaged.
5.Warning-To reduce the risk of injury, user must read instructions manual carefully.
6.The product complies with relevant standards and regulations. Installation of this device must comply with all applicable regulations, and it should only be operated in well-ventilated areas. Please read the user manual before installing and using this equipment.
7.Children shall not play with the appliance.
8.Please properly keep product. Check whether the product is abnormal before use. If it is abnormal, please stop using it.
9.Please use the product according to the intended use, warn of potential injury from misuse.

PARTS LIST

ITEM	Name	Reference Image	Q'TY	ITEM	Name	Reference Image	Q'TY
A	Bent rod		1PCS	E	Repair pen		1PCS
B	white ball		1PCS	F	Replace head		7PCS

C	Rubber Hammer		1PCS	G	Air bag		1PCS
D	Disassemble the pen		1PCS	H	Manual		1PCS

OPERATION

1.Confirm the range of the dent.



2.Remove the inside fender.





3.Install a white ball on the pry bar.



4.Insert crowbar and aim the back side of the dent, push the dent out, then dent disappears.



5.Hammer high point, then high point disappears.



AIRBAGS INSTRUCTIONS



1. Place the airbag in the appropriate position, squeeze and inflate it to the appropriate position, and use tools to repair it.





2. After completing the repair, remove the airbag air through the release valve and take out the airbag.

